


A7700 & AF7700 Rim Type Panic and Fire Exit Devices (ADA) A7760V & AF7760V Vertical Rod Panic and Fire Exit Devices (ADA) ANSI A156.3, Grade 1



Features & Construction

- ◆ **Retrofits Von Duprin 99 & 98 Series using 7700 Escutcheon Trim**
- ◆ Americans with Disability Act (ADA) compliant. 5lbs opening force on ADA product only
- ◆ For use in institutions, schools, universities, commercial buildings where heavy duty reliable operation is a requirement
- ◆ ANSI A156.3, Grade 1 heavy duty exit device in surface vertical rod and rim designs
- ◆ Rail assemblies are heavy duty extruded aluminum body with Stainless Steel push pad and end caps are made of brass, bronze or stainless steel. Rail travels in direction of the door swing
- ◆ Trims are thru-bolted for additional security
- ◆ Conforms & Meets ADA Regulations

CONFIGURATION	MAX FRAME DIMENSIONS	LOCK TYPE	DESIGN PRESSURE (PSF) OUTSWING	
			POSITIVE	NEGATIVE
SINGLE	40" x 88"	F7700V SERIES F7700 SERIES	+70.0	-70.0
	52" x 98"		+50.0	-50.0
DOUBLE	76" x 88"	F7700V SERIES	+70.0	-70.0
	100" x 98"		+50.0	-50.0

- ◆ UL Listed for Panic and ULC10C, UBC 7-2-1997 codes
- ◆ UL Listed for Fire Exit Hardware. 3 hours
- ◆ (A) label rating on pairs of doors up to 8'0" x 8'0" swinging in same or opposite directions
- ◆ Uncompromising security and safety in single and double fire exit doors
- ◆ Chassis mounted unit construction. Rim and vertical rod devices are non-handed and easily reversible
- ◆ Available in many different functions. Lever and escutcheon trims are grade 1 construction with clutch on rose trims. Escutcheon trims are rigid and covers 161 cut out.


Suggested Architect's Specifications

- ◆ All exit devices shall be of touch bar design with smooth operation and be operative over $\frac{2}{3}$ of the door's clear opening width
- ◆ All exit devices must be listed under "Panic Hardware" in the Accident Equipment List of Underwriters' Laboratories, Inc. Where labeled doors are used as exits, they must be equipped with labeled Fire Exit Hardware and UL10C, UBC 7-2-1997 codes
- ◆ All springs shall be of Stainless Steel throughout
- ◆ All exit devices shall be of chassis mounted unit construction.
- ◆ All exit devices shall be ANSI A156.3, Grade 1

A7700 & AF7700 ADA Series
GRADE 1, Rim Type Exit Device



LIFETIME WARRANTY, BHMA CERTIFIED, MEETS The Buy American Act, ADA COMPLIANT, UL US 3 HOUR FIRE RATED UL10C, UBC7-2-1997



Specifications

Table with 2 columns: Specification and Description. Rows include: For Doors, Chassis, Cover, Mounting, End Cap, Alarm, Hand, Latch Bolt, Spring, ANSI Standard, Rail Assembly, Strike, Dogging Feature, Mullion, UL and ULC Listed, Finish, Electronic Functions, Anti-Microbial Coating.



*Americans with Disability Act (ADA) compliant
5 lbs opening force on ADA Series only
*Refer to the Price List for Stock Sizes and Finishes

4 1/2" Minimum Stile Requirements




Table with 2 main sections: DIMENSIONS and MODEL. Dimensions include touchbar height, projection, and center case. Model table lists actual length, max cut down, and door size for various models.