

Meets ANSI/BHMA A156.9

**CL21 Ball Catch**


- Four-way catch with hexagon stud.
- Ideal for holding medium duty doors.
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut.
- Strike can enter body from any direction.
- Spring tension is easily adjusted to suit field conditions.
- Body can be surface applied or mortised.
- Brass construction.

**Dimensions**

Body: 3/4" Wide x 3" High x 3/4" Deep  
 Strike: 3/4" Wide Hex x 1-1/2" High

**Finishes** *brass*

Ives Number	US26D
BHMA	626



Meets ANSI/BHMA A156.9, B13292

**CL21A Ball Catch**

- Four-way catch with plate type strike.
- Ideal for closet doors, access doors, hinged openings and numerous other applications.
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut.
- Strike can enter body from any direction.
- Spring tension is easily adjusted to suit field conditions.
- Body can be surface applied or mortised.
- Brass construction.

**Dimensions**

Body: 3/4" Wide x 3" High x 3/4" Deep  
 Strike: 7/16" Wide x 1-3/4" High x 7/8" Deep

**Finishes** *brass*

Ives Number	US3	US4	US10	US26	US26D
BHMA	605	606	612	625	626



Meets ANSI/BHMA 156.9, B13302.

**CL22 Ball Catch**

- Three-way catch with plate type strike.
- Ideal for smaller cabinet doors or panels.
- The strike slides between two stainless steel balls that are under spring tension. As the strike engages, the door is held tightly shut.
- Strike can enter body from either side or front.
- Spring tension is easily adjusted to suit field conditions.
- Body can be surface applied or mortised.
- Brass construction.

**Dimensions**

Body: 1/2" Wide x 2-3/16" High x 1/2" Deep  
 Strike: 3/8" Wide x 1-3/8" High x 5/8" Deep

**Finishes** *brass*

Ives Number	US3	US4	US10	US26	US26D
BHMA	605	606	612	625	626