

ECL EXIT CONTROL HARDWARE



Factory installed rim cylinders shown (specify RC65)

- Rugged, dependable and proven alarmed exit device for secondary exits (ECL-230D and ECL-230D-PH)
- Code-compliant, rugged, dependable fire rated relatching alarmed exit device for secondary exits (ECL-600)
- Approximately 100dB piezo alarm
- 9-volt battery
- 1" throw, saw resistant deadbolt (ECL-230D and ECL-230D-PH)
- 1" throw, saw resistant deadbolt and deadlocking latchbolt provide 2-point locking (ECL-600)
- Resists over 2200 lbs outside pull force
- Photoluminescent metal paddle sign
- Tamper resistant housing with cover lock
- For weatherized applications see ECL-230X Series
- Non-handed
- Available in 2 colors - gray or black (ECL-230D and ECL-230D-PH)
- Optional ECL-620 outside lever trim (ECL-600)
- Optional two-point locking (see VRA-143) - For ECL-230D & PH only)
- Optional bar guard kits (specify ECL-436K or ECL-2100K)
- Signage available in many languages
- U.L. Listed panic hardware (ECL-230D and ECL-230D-PH)
- Warnock Hersey Labeled fire exit hardware for 3 hours, single or pairs of doors (ECL-600)
- Exceeds all Life Safety, ADA, California Title 19, ANSI/BHMA requirements for all building codes
- Ten year limited warranty



EXIT CONTROL HARDWARE ACCESSORIES

VERTICAL ROD ASSEMBLY (VRA-143)

- Sturdy assembly for use with ECL-230 to provide security on single or pairs of doors up to 10' where two-point locking is required. U.L. LISTED
- Heavy-duty, 3/8" diameter locking bolts

DX BOLTS

- Provides hinge-side protection as an additional line of defense against break-ins
- One piece construction provides superior holding strength
- Kits of 1 bolt, 2 bolts or 3 bolts include through-bolt mounting hardware
- Add DX bolts to any Detex multi-point lock to create 4 point, 5 point and 6 point locks
- Excellent for exterior applications or doors that get wet

