

# SPECIFICATIONS FOR HOLLOW METAL DOORS 86 PREP POLYSTYRENE CORE


Doormart USA has a full range of hollow metal doors. Standard doors are 1 3/4" in thickness and are available in 16, 18 and 20 gauge. Door skins are mechanically interlocked vertically along the hinge and lock edge. Door edges are beveled 1/8" in 2" and door surfaces are flush and free of any joints welds or seams. All standard doors are manufactured from galvanized steel and are prepared and reinforced to receive specified architectural hardware in accordance to ANSI A115 Standards.

## Top Channel

18 gauge inverted end channel is spot welded to door skins and tack welded at each corner of the door for extra rigidity.


## Door Closer Reinforcement

18 gauge door closer reinforcement box is laminated to inside of door skins.




## 86 MORTISE LOCK PREP

Government Series 86 edge door prep is reinforced with a 18 gauge reinforcement box with integrated clips to help hold mortise lock in proper position in accordance to ANSI A115.1 requirements.



## POLYSTYRENE CORE

Rigid extruded fire retardant, closed cell board. Density; 1 to 2 pcf (16 to 32 kg/m<sup>3</sup>), thermal values; R6.0 (RSI 1.05) min.



## HINGE REINFORCEMENT

10 gauge high frequency hinge reinforcement with return bend for added strength.

## Bottom Channel

18 gauge inverted end channel is spot welded at each corner of the door for extra rigidity.

