Pull plate 8302

Available mounting – Standard, F, G, H-I-L, or J see pages B15 and B16 Pulls have new heavy duty 5/16-18" mounting.

8102 Pull
6" centers
8" centers
10" centers

Finishes brass

US Number	US3	US4	US10	US10B	US26	US26D*	
ВНМА	605	606	612	613	625	626	

Finishes sta	inless steel	Finishes aluminum		
US Number	US32D*	US Number	US28	
BHMA	630	BHMA	628	

^{*} Available with Antimicrobial Coating, use suffix AM

8303 **Pull plate**

Available mounting – Standard, F, G, H-I-L, or J see pages B15 and B16 Pulls have new heavy duty 3/8-16" mounting.

8300 Plate	8103 Pull
3-1/2" x 15"	8" centers
4" x 16"	10" centers
6" x 16"	7" centers

Finishes brass

US Number	US3	US4	US10	US10B	US26	US26D*
BHMA	605	606	612	613	625	626

Finishes sta	inless steel	Finishes aluminum		
US Number	US32D*	US Number	US28	
BHMA	630	ВНМА	628	

^{*} Available with Antimicrobial Coating, use suffix AM

8305 **Pull plate**

Available mounting – Standard or F see page B15 Pulls have 1/4 - 20" mounting


8300 Plate	8105 Pull
3-1/2" x 15"	6" centers
4" x 16"	8" centers
6" x 16"	10" centers


Finishes brass

US Number	US3	US4	US10	US10B	US26	US26D	
BHMA	605	606	612	613	625	626	

Finishes sta	inless steel	Finishes aluminum		
US Number	US32D	US Number	US28	
ВНМА	630	BHMA	628	

^{*} Available with Antimicrobial Coating, use suffix AM








Mounting

- All mounting hardware is for standard 1-3/4" door.
- · Consult Customer Service if other than standard.


Type Standard Mount



Standard Mounting

- (2) 3/8-16 x 2-1/4" brass, flat head machine screws; plate to match.
- (2) 3/8-16 countersunk washers; plated to match
 Note: 8102HD and 8105 have (2) 5/16-18 x 2-1/2" machine screws
 -Options: (2) 5/16 countersunk washers

Type G Mount



Concealed Pull Plate Mounting

Available only for 8302, 8303, 8311 Pull Plates.


• (2) 3/8-16 x 5/8" steel flat head machine screws; zinc plated.

Pull mounts directly onto plate.

Plate is attached to door by 6 screws.

Note: 8302 has (2) 5/16-19 x 5/8" steel flathead zinc plated screws

Type F Mount




Wood Doors Concealed Pull Mounting With Push Plate

• (2) 2-1/4" steel flat head machine screws; zinc plated.

Available only for 8102HD, 8103HD, 8105, 8111, 8302, 8303, 8305 and 8311. Plate on opposite side of door must be ordered separately.

Note: 8102HD, 8302 will have 5/16-18 8105, 8111, 8305, 8311 will have 1/4-20 8103HD, 8303 will have 3/8-16"

Type H-I-L Mount



Reinforced Hollow Metal Door Concealed Pull Mounting

Available only for 8102, 8103, 810EZ or wood door pulls, 8302, 8303 pull plates and 9264, 9265, 9266 and 9267 long door pulls.

- (2) Steel screw sleeves; zinc plated.
- (2) Steel countersunk trim head machine screw; zinc plated for reinforced metal door.
- (2) Steel countersunk trim head steel metal screw; zinc plated for wood doors.

Note: 8102HD and 8302 will have 5/16-18" 8103HD, 8103EZHD, 8303 will have 3/8-16